

**Trafa B.V.**  
Tussendonk 13  
NL 4878 AM Etten-Leur  
Tel. +31 (0)76 501 3451  
Fax +31 (0)76 502 1454  
E-mail info@trafa.nl  
Internet www.trafa.nl



# Request for Quotation battery charger

Print current document and fill out the following information as completely as possible and fax it to +31765021454 or e-mail to sales@trafa.nl.

COMPANY NAME : .....

ADDRESS : .....

ZIP CODE : .....

CITY : .....

COUNTRY : .....

TELEPHONE. : .....

FAX : .....

E-MAIL : .....

CONTACT : .....

Trafa B.V.  
Tussendonk 13  
NL 4878 AM Etten-Leur  
Tel. +31 (0)76 501 3451  
Fax +31 (0)76 502 1454  
E-mail info@trafa.nl  
Internet www.trafa.nl



**OFFER SHEET BATTERYCHARGER**

Name Project

- 1 – Phase
- 3 – Phase

Supply Voltage  V

Frequency  Hz

Battery DC voltage  V

Capacity  Ah

- Type Battery
- Lead (Pb)
  - Nickelcadmium (NiCd)

Maximum charging current  A

Maximum charging voltage  V ( standard 30 V )

Maximum ambient temperature > 40 °C  °C

- Land construction
- Tropical construction
- Ship construction

- If ship construction choose
- IEC 92-5
  - ABS
  - BV
  - DNV
  - GLRoS
  - LroS
  - Rina
  - Other

Number of batterychargers  Piece(s)

**Delivery :**

- Mounted on ground plate
- In cabinet

- Open construction
  - Wallmounting
  - FloormountingProtection degree IP00. Terminals IP20. When the terminals do not suffice, a cover will be applied to prevent accidental contact

- Closed construction
  - Wallmounting
  - Floormounting

- Protection degree IP23 (standard)
- Higher protection degree on request IP

Remarks