

Trafa B.V.
Tussendonk 13
NL 4878 AM Etten-Leur
Tel. +31 (0)76 501 3451
Fax +31 (0)76 502 1454
E-mail info@trafa.nl
Internet www.trafa.nl



Request for Quotation choke

Print current document and fill out the following information as completely as possible and fax it to +31765021454 or e-mail to sales@trafa.nl.

COMPANY NAME :

ADDRESS :

ZIP CODE :

CITY :

COUNTRY :

TELEPHONE. :

FAX :

E-MAIL :

CONTACT :

OFFER SHEET CHOKE

Name project

- 1 – Phase
- 3 – Phase
- DC
- AC
- Air choke (1 – phase)

Self-inductance μ H mH H

(Ripple) Frequency Hz

Current A

Systemvoltage V

Fill in if chosen DC

- Ripple voltage A
- or
- Ripple voltage V

Max. ambient temperature > 40°C °C 40 ° C is standard

- Land construction
- Tropical construction
- Ship construction

- If ship construction choose :
- IEC 92-5
 - ABS
 - BV
 - DNV
 - GLRoS
 - LroS
 - Rina
 - Other

- Open construction
 - Wallmounting
 - Floormounting
- Closed construction
 - Wallmounting
 - Floormounting

Protection degree IP00. Terminals IP20. When the terminals do not suffice, a cover will be applied to prevent accidental contact.

- Protection degree IP21 (standard)
- Protection degree IP23 (standard)
- Higher protection degree on request

- Color cabinet (standard)
- Other RAL Standard = RAL 7035. Other RAL-colors against extra charges.

Number of chokes Piece(s)

Remarks