

Trafa B.V.
Tussendonk 13
NL 4878 AM Etten-Leur
Tel. +31 (0)76 501 3451
Fax +31 (0)76 502 1454
E-mail info@trafa.nl
Internet www.trafa.nl



Request for Quotation startertransformer

Print current document and fill out the following information as completely as possible and fax it to +31765021454 or e-mail to sales@trafa.nl.

COMPANY NAME :

ADDRESS :

ZIP CODE :

CITY :

COUNTRY :

TELEPHONE. :

FAX :

E-MAIL :

CONTACT :

Trafa B.V.
 Tussendonk 13
 NL 4878 AM Etten-Leur
 Tel. +31 (0)76 501 3451
 Fax +31 (0)76 502 1454
 E-mail info@trafa.nl
 Internet www.trafa.nl



OFFER SHEET STARTERTRANSFORMER

Name project

RATED MOTORDATA

Rating (Squirrel cage motor) kWatt

Voltage V

Frequency Hz

Nominal Current A

Direct on line current (Idol) A

REQUIRED STARTER TRANSFORMER SPECIFICATION

Number of starts per hour Times

Number of starts in succession Times

Starting time per start Sec. Starting time of the motor (if applicable included instrument) on the nominal tapping.

Required starting current reduction :

o Starting current limitation on nominal tapping maximum A Starting current in power supply

or
 o Starting current limitation on nominal tapping %

Maximum ambient temperature > 40 °C °C 40 ° C is standard

- o Land construction
- o Tropical construction
- o Ship construction

If ship construction choose :

- o IEC 92-5
- o ABS
- o BV
- o DNV
- o GLRoS
- o LroS
- o Rina
- o Other

o Open construction

- o Wallmounting (if possible)
- o Floormounting

Protection degree IP00. Terminals IP20. When the terminals do not suffice, a cover will be applied to prevent accidental contact

o Closed construction

- o Wallmounting (if possible)
- o Floormounting

Trafa B.V.
Tussendonk 13
NL 4878 AM Etten-Leur
Tel. +31 (0)76 501 3451
Fax +31 (0)76 502 1454
E-mail info@trafa.nl
Internet www.trafa.nl



- Protection degree IP21 (standard)
- Protection degree IP23 (standard)
- Higher protection degree on request

- Color cabinet (standard)
- Other RAL Standard = RAL 7035. Other RAL-colors against charges

Number of startertransformers Piece(s)

Extra specifications:

Deviated tappings at % Standard at +5% and -5% at nominal tap

Standard temperaturedevice 1 pc. bi-metal (N.C.) 250V – 50 Hz – 3A in centre coil

Deviated number pcs.

- Deviated type
- PTC
 - PT100 (3-wire)
 - Other

Remarks